

GPU A+ Server AS -4125GS-TNRT



Key Applications

AI / Deep Learning, High Performance Computing,

Key Features

- Flexible GPU support: active & passive GPUs; Up to 8 direct attached double width, full length GPUs;
- AMD EPYC[™] 9004 Series Processor up to 360W TDP; Dual-Socket, AMD EPYC[™] 9004 Series Processors up to 360W TDP;
- 24 DIMM Slots, up to 6TB DDR5 memory; 12 DIMM Slots, up to 3TB DDR5 memory;
- up to 4x 2.5" Hot-swap NVMe drive bays; 1 M.2 Slot;
- AIOM / OCP 3.0 Support;




Form Factor	4U Rackmount
	Enclosure: 437 x 178 x 737mm (17.2" x 7" x 29")
	Package: (27" x 26.57" x 41")
Processor	Dual Socket SP5
	AMD EPYC™ 9004 Series Processors
	Up to 128C/256T
GPU	Max GPU Count: Up to 8 double-width GPU(s)
6. 6	Supported GPU:
	AMD PCIe: Instinct MI210
	NVIDIA PCIe: H100 NVL,H100,RTX 4000 ADA,L40,RTX A4000,RTX 5000,L40S,A40,A100,RTX A5500,RTX 6000,A30
	CPU-GPU Interconnect: Direct Attached
	GPU-GPU Interconnect: NVIDIA® NVLink® Bridge (optional), AMD Infinity Fabric™ Link (optional)
	GPO-GPO Interconnect: NVIDIA- NVLITIK- Bridge (optional), AMD ITITITITY PADRIC LITTIK (optional)
System Memory	Slot Count: 24 DIMM slots
	Max Memory (1DPC): Up to 6TB 4800MT/s ECC DDR5 RDIMM/LRDIMM
Drive Bays	24x 2.5" hot-swap NVMe/SATA/SAS drive bays (4x 2.5" NVMe dedicated)
	1 M.2 NVMe
Expansion Slots	9 PCle 5.0 x16 FHFL slot(s)
On-Board Devices	SATA: SATA3 (6Gbps)
	Chipset: AMD SP5
	Network Connectivity: 2x 10GbE BaseT
	IPMI: Support for Intelligent Platform Management Interface v.2.0
	IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Input / Output	Video: 1 VGA port(s)



(Front View - System)





System Cooling	Fans: 8 heavy duty fans with optimal fan speed control
Power Supply	4x 2000W Redundant Titanium Level power supplies
System BIOS	BIOS Type: AMI 32MB SPI Flash EEPROM
Management	Redfish API; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); SuperDoctor® 5; Super Diagnostics Offline; KVM with dedicated LAN; IPMI 2.0
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory 7+1 Phase-switching voltage regulator FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Height: 7" (178 mm) Width: 17.2" (437 mm) Depth: 29" (737 mm) Gross Weight: 100 lbs (45.3 kg) Net Weight: 65.5 lbs (29.7 kg) Packaging: 26.57" x 27" x 41" Available Color: Black Front & Silver Body
Operating Environment	Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	Super H13DSG-O-CPU
Chassis	CSE-418G2TS